



CABLE AND MOUNTING CLIPS FIRE RESISTANT CONDUIT CLIPS



LINIAN CONDUIT SUPERCLIP

DESCRIPTION

The LINIAN Conduit SuperClip is perfect for armoured cables, conduit and bunched cables.

The SuperClip has a closed head design with a neat, tidy finish. The patented LINIAN design includes a closed head/loop to secure the cable. If there is any tension on the wire, the clip won't pop open and release the cable.

LINIAN clips feature barbed legs which expand in the hole to grip the substrate, providing a secure fixing. The legs are strong but flexible and won't snap under pressure. They work with substrates including brick, concrete, wood and even plasterboard.

The SuperClip is available in sizes 18-20 mm and 23-25 mm in white or a galvanised colour.

The LINIAN Conduit SuperClip is fast becoming the industry standard and meets all current industry regulations, including British Standards; BS7671 : Amendment 3; BS7671 : 18th Edition 2018; BS EN50200 PH120; BS8519 : 2010; as well as European Standard DIN 4102-12 E90.

FEATURES

- 70% quicker installation
- 90 & 120 minute fire resistant, meeting BSi and DIN classifications
- Corrosion resistant and UV stable
- Suitable for indoor and outdoor use
- Safe working load of 44 kg
- Suitable for conduit and bunched cables to ensure neat cable installation
- Suitable for armoured cable and trunking
- Anchor fixings for wire and bunched cable
- No need for conduit saddles
- Can be used with steel cable ties





CABLE AND MOUNTING CLIPS FIRE RESISTANT CONDUIT CLIPS

SPECIFICATIONS

Tensile Load	44 kg
Accommodating Width	12-25 mm (for cables and conduits)
Conduit Size	Recommended clip size (Galvanised and White)
20 mm	18-20 mm SuperClip
25 mm	23-25 mm SuperClip

ORDERING INFORMATION

Product Code	Product Description
LC-SCLIP20-GAL	Conduit SuperClip, Galvanised, 18-20 mm (25 Pack)
LC-SCLIP20-W	Conduit SuperClip, White, 18-20 mm (25 Pack)
LC-SCLIP25-GAL	Conduit SuperClip, Galvanised, 23-25 mm (25 Pack)
LC-SCLIP25-W	Conduit SuperClip, White, 23-25 mm (25 Pack)

• **DISCLAIMER:** Although the contents of our product literature have been prepared with the greatest care, Technoswitch can accept no liability whatsoever for any direct or indirect damages of any kind that may arise due to either errors or omissions in them, or amendments to products or other specifications following publication.

© Technoswitch (Pty) Ltd



HEAD OFFICE — JOHANNESBURG
Cussonia Park, 3 Ridge Road, Laser Park, Johannesburg **T** +27 (0)11 794 9144 **E** info@technoswitch.co.za
CAPE TOWN **T** +27 (0)21 948 4575 ■ **DURBAN** **T** +27 (0)31 266 8843

www.technoswitch.co.za

Document: DS LC-SCLIP 210503 E & OE