



WARNING DEVICES – CONVENTIONAL

SONOS SOUNDERS



SONOS SOUNDER DC
SHALLOW BASE



SONOS SOUNDER AC
DEEP BASE

SONOS SOUNDER DC

A general purpose electronic sounder featuring the TimeSaver base, where connections are made to the base during the initial wiring phase, resulting in faster and more reliable installation.

The sounder head 'twists and clicks' into the base on commissioning, avoiding the wiring and connection problems associated with traditional sounders.

Deep base units have weatherproof protection to IP65 and can be used both indoors and outdoors.

Sonos Sounder units are available in either red or white (the white option is available on special order) with a choice of deep or shallow TimeSaver bases.

SONOS SOUNDER AC – KL-SO-SRW220

A general purpose AC electronic sounder for industrial applications.

With a choice of 32 tones including all the major European standards, Sonos is accepted universally.

The Sonos AC sounders are weatherproof to IP65 and suited for indoor and outdoor use.

The units are available in either red or white (the white option is available on special order).

FEATURES

SONOS SOUNDER DC

- EN54 Compliant
- Wide voltage range
- Simple "First Fix" installation
- 2 alarm stages
- 32 tones
- Tone and volume can be preset or adjusted off-base
- Shallow Base: Weatherproof to IP21
- Deep Base: Weatherproof to IP65
- Synchronised alarm tones
- Volume control typical 8 dB

SONOS SOUNDER AC

- Complies to EN60950
- Dual Voltage 110 V AC or 230 V AC
- Up to 102 dBA at 1 metre
- Deep Base: Weatherproof to IP65
- Synchronised alarm tones
- Volume control 20 dB





WARNING DEVICES – CONVENTIONAL

SONOS SOUNDERS

SONOS SOUNDER DC – KL-SO-SR & KL-SO-SRW

Supply Voltage Range	9-60 V DC
Current	4-41 mA*
Peak Sound Level	94-106 dBA at 1 metre*
Number of Tones	32
Operating Temperature	-25 °C to +70 °C
Casing	High Impact Polycarbonate
IP Rating	
Shallow Base	IP21
Deep Base	IP65
Weight	
Shallow Base	220 g
Deep Base	250 g
Dimensions	
Shallow Base	Ø 100 mm, h 80 mm
Deep Base	Ø 97.5 mm, h 104 mm (incl Base)
Compliance	
Shallow Base	EN 54-3 Type A (Indoor)
Deep Base	EN 54-3 Type B (Outdoor)

SONOS SOUNDER AC – KL-SO-SRW220

Supply Voltage Range	110-230 V AC
Peak Sound Level	94-106 dBA at 1 metre*
Number of Tones	32
Operating Temperature	-25 °C to +55 °C
Casing	Flame Retardant Polycarbonate
IP Rating	IP65
Weight	250 g
Dimensions	Ø 97.5 mm, h 104 mm (incl Base)
Cable Entries	2x 20 mm Cable Glands
Compliance	EN 60950

* depends on selected tone and input voltage

ORDERING INFORMATION

Product Code	Product Description
KL-SO-SR	Sounder, Red, Shallow Base, 100 dB, 9-60 V DC
KL-SO-SRW	Sounder, Red, IP65, 100 dB, 9-60 V DC
KL-SO-SRW220	Sounder, Red, IP65, 100 dB, 110-230 V AC

• **DISCLAIMER:** Although the contents of our product literature have been prepared with the greatest care, Technoswitch can accept no liability whatsoever for any direct or indirect damages of any kind that may arise due to either errors or omissions in them, or amendments to products or other specifications following publication. © Technoswitch (Pty) Ltd



HEAD OFFICE — JOHANNESBURG
Cussonia Park, 3 Ridge Road, Laser Park, Johannesburg T +27 (0)11 794 9144 E info@technoswitch.co.za
CAPE TOWN T +21 948 4575 DURBAN T +27 (0)31 266 8843

www.technoswitch.co.za

Document: DS KL-SO Sounders 210&31 E & OE