



WARNING DEVICES – CONVENTIONAL BEACONS



**SONOS LED
BEACON
SHALLOW BASE**



**SONOS XENON
BEACON
DEEP BASE**

SONOS LED BEACON (DC)

A general-purpose beacon for fire, security and industrial applications.

Connections are made to the TimeSaver base during the initial wiring phase, resulting in faster and more reliable installations. The sounder head “twists and clicks” into the base on commissioning, avoiding the wiring and connection problems associated with traditional sounders.

Deep base units have weatherproof protection to IP65 and can be used both indoors and outdoors.

The Sonos Beacon utilises a full-faced, translucent case which provides a much larger lens area and a greater spread of light.

Sonos Beacon units have a deep or shallow red colour base as standard and are available with a red (or amber on special order) lens.

SONOS XENON BEACON (AC) – KL-SO-HPXR220

A general purpose, high output xenon beacon designed for industrial applications.

Sonos xenon beacons are weatherproof to IP65 and can be used both indoors and outdoors.

The Sonos xenon beacon unit utilises a full-faced, translucent case rather than a separate add-on beacon, giving a much larger lens area. This results in a far greater light spread for more effective warning.

Sonos Beacon units have a red colour base as standard and are available with a red lens (amber, clear, green and blue lenses available on special order).

FEATURES

SONOS LED BEACON (DC)

- High-efficiency LED beacon
- Consumes less than 5 mA
- Simple “First Fix” installation (no second fix wiring)
- Shallow Base: Weatherproof to IP21
- Deep Base: Weatherproof to IP65
- Synchronised flash

SONOS XENON BEACON 5J (AC)

- High output 5J xenon beacon
- 10-60 V DC or 110-230 V AC
- Simple “First Fix” installation
- Deep Base: Weatherproof to IP65
- No surge current



WARNING DEVICES – CONVENTIONAL BEACONS

SPECIFICATIONS

SONOS LED BEACON (DC)

IP Rating	
Shallow Base	IP21
Deep Base	IP65
Rating	Continuous
Operating Temperature	-25 °C to +70 °C
Construction	Flame Retardant Polycarbonate
Cable Entries	
Deep Base	2x 20 mm cable glands
Weight	
Shallow Base	220 g
Deep Base	250 g
Colours	Red base, red lens
Voltage	17-60 V DC
Current	5 mA
Dimensions	
Shallow Base	Ø 100 mm, h 80 mm
Deep Base	Ø 97.5 mm, h 104 mm (incl Base)

SONOS XENON BEACON (AC) – KL-SO-HPXR220

IP Rating	IP65
Operating Temp	-25 °C to +55 °C
Construction	Flame Retardant Polycarbonate
Cable Entries	2x 20 mm cable glands
Weight	250 g
Compliance	EN 60950
Colours	Red base, red lens
Voltage	110-230 V AC
Current	70 mA
Dimensions	Ø 97.5 mm, h 104 mm (incl Base)

ORDERING INFORMATION

Product Code	Product Description
KL-SO-BR	Beacon, Red Shallow Base, 17-60 V DC
KL-SO-BRW	Beacon, IP65, Red, 17-60 V DC
KL-SO-HPXR220	Sonos Beacon, IP65, 110-230VAC, High Power 5J Xenon, Red

• **DISCLAIMER:** Although the contents of our product literature have been prepared with the greatest care, Technoswitch can accept no liability whatsoever for any direct or indirect damages of any kind that may arise due to either errors or omissions in them, or amendments to products or other specifications following publication. © Technoswitch (Pty) Ltd



HEAD OFFICE — JOHANNESBURG
Cussonia Park, 3 Ridge Road, Laser Park, Johannesburg T +27 (0)11 794 9144 E info@technoswitch.co.za
CAPE TOWN T +21 948 4575 DURBAN T +27 (0)31 266 8843

www.technoswitch.co.za

Document: DS KL-SO Beacons 210831 E & OE