



TEST EQUIPMENT

SOLO 365 SMOKE DETECTOR TESTER



**SOLO 365
DETECTOR TESTER**

DESCRIPTION

The Solo 365 is lighter to use, quicker to test, suitable for more applications and almost impossible to over-apply, eliminating the risk of detector contamination.

Solo 365 offers everything the industry has come to expect from the Solo brand, pairing it with the very latest technology and wrapping it in a new modern slim-line design and incorporates non-hazardous, non-pressurised cartridges.

Engineered to be compatible with the increasing number of sophisticated detectors now available, the Solo 365 also overcomes the regulatory issues associated with pressurised aerosol canisters.

By fitting the ASD Test Adapter to Solo 365 in place of the standard clear cup, Solo 365 now also enables functionally testing of ASD systems – allowing the ability to test both standard point type smoke detectors and ASD systems with one portable tester.



FEATURES

- Proximity Sensor – Automatic generation of smoke as the detector enters and leaves the cup
- Clear Cup & Vent – Allows easy viewing of the detector during testing and ensures smoke is quickly removed after testing
- LED Torch – Automatically illuminates when light levels drop, allowing easy alignment with detector
- Consumables Compartment – Neatly houses all consumables, enabling easy replacement
- Function Button/Delayed Start Mode – Perfect for testing ASD systems or detectors which cannot enter the cup
- Status LEDs – Provides notification of unit mode status
- Optional ASD Adapter



TEST EQUIPMENT

SOLO 365 DETECTOR TESTER

SPECIFICATIONS

Operating Features

Colour coded LED user information
Proximity sensor starts test
Suitable for detectors up to 110 mm diameter
5 seconds of stimulus, 5 seconds off repeat cycles

Safety Features

Battery over current cut-out
Over temperature cut-out
2 minutes maximum duration time-out
Auto power off after 10 minutes

Power Source

Lithium ion battery pack nominal 3.63 V 9.5 Wh, with USB charger connection

Battery Charging Time

±2 hours

Operating Temperature Range

+5 °C to 45 °C

Operating Humidity Range

0 to 85% RH non-condensing

Storage Temperature Range

-10 °C to 50 °C

Storage Humidity Range

0 to 90% RH non-condensing

Weight

860 g

Dimensions H x W x D

420 x 190 x 110 mm (including handle)

Dimensions H x W x D

295 x 190 x 110 mm (excluding handle)

Dimensions with Cup in user position

260 x 190 x 150 mm

Clear Cup Dimensions

150 x 85 mm

ORDERING INFORMATION

Product Code

DT-SOLO365-KIT1
DT-SOLO365-SC12
DT-SOLO365-ASD

Product Description

Solo365 Electronic Smoke Detector Tester Kit
Solo365 Smoke Cartridge (pack of 12)
Solo365 ASD Test Adapter

SPARES

Product Code

DT-SOLO-220CH
DT-SOLO-BATON

Product Description

220/240 V AC Mains & Car Charger for SOLO Battery Baton
Battery Baton for SOLO Cordless Heat Detector Tester

■ **DISCLAIMER:** Although the contents of our product literature have been prepared with the greatest care, Technoswitch can accept no liability whatsoever for any direct or indirect damages of any kind that may arise due to either errors or omissions in them, or amendments to products or other specifications following publication.

© Technoswitch (Pty) Ltd



HEAD OFFICE — JOHANNESBURG
Cussonia Park, 3 Ridge Road, Laser Park, Johannesburg **T** +27 (0)11 794 9144 **E** info@technoswitch.co.za
CAPE TOWN T +21 948 4575 **DURBAN T** +27 (0)31 266 8843

www.technoswitch.co.za

Document: DS-DT-SOLO365 201015 E & OE