





APOLLO TEST SET

DESCRIPTION

The Apollo Test Set is a portable testing device, to assist commissioning and system maintenance engineers – and to guarantee that the correct loop configuration is in place before an active control panel is installed. It can interrogate and control all units connected to the device, either as individual units or complete circuits.

Software updates are easily installed in the field using built-in USB connectivity.

The test set is compatible with Apollo XP95, Discovery and CoreProtocol (Soteria) protocols and carries a 10 year warranty.

With a user-friendly seven-inch LCD touch screen display, the test set comes in a robust carry case, complete with universal charger, connector cables, XPERT 8 intelligent mounting base and carry strap.

The test set is designed for indoor use only and should not be subjected to harsh environments. It is not suitable for use in hazardous areas (those containing explosive vapour or dust), or in places where temperatures and/or humidity are high or go through rapid changes.

EMC DIRECTIVE 2014/30/EU

The Apollo Test Set complies with the essential requirements of the EMC Directive 2014/30/EU, provided that it is used as described in this data sheet.

A copy of the Declaration of Conformity is available upon request.

Conformity of the Apollo Test Set with the EMC Directive does not confer compliance with the directive on any apparatus or systems connected to it.

FEATURES

- Loop connection ports for individual addressing or fault finding
- Enables loop integrity and diagnostics testing during commissioning and maintenance
- View device information and control functionality modes
- Lithium-ion battery powered, complete with multi-regional mains adaptor
- Seven-inch LCD touch screen display
- Choice of languages
- USB connectivity
- Software updates via the Apollo website
- Compatible with XP95®, Discovery® and CoreProtocol® (Soteria®) ranges
- 10 year warranty









SPECIFICATIONS

Power Source Lithium-ion battery pack or 12 V Power Supply Unit

Battery Charging Time Approximately 3 hours

Operating Temperature $0 \, ^{\circ}\text{C}$ to $40 \, ^{\circ}\text{C}$ Humidity (No Condensation or Icing) $10 \text{ to } 95 \, \% \text{ RH}$ Dimensions (W x H x D) $215 \, \text{x} \, 165 \, \text{x} \, 50 \, \text{mm}$

Weight 935 g







ORDERING INFORMATION

Product Code Product Description

AP-TESTSET Apollo Test Set

• DISCLAIMER: Although the contents of our product literature have been prepared with the greatest care, Technoswitch can accept no liability whatsoever for any direct or indirect damages of any kind that may arise due to either errors or omissions in them, or amendments to products or other specifications following publication.

