

STEEL SURFACE MOUNT BACK-BOX



The VS-EVS-ACBBS is a Single Gang 41 mm deep metal back-box suitable for use with the **ASSIST CALL range** of devices.

It is ideal for surface fixing onto brick or block walling. The curvature of the corners is matched exactly to the product.

PLASTIC FLUSH MOUNT BACK-BOX

- The VS-EVS-ACBBF Single Gang 35 mm Dry lining Box is ideal for fast fixing into cavity wall structures, dry lining partitions and plaster board up to 15 mm thick.
- Manufactured from flame retardant thermoplastic, keeping electric elements protected in the event of a fire, even after the structural integrity of the wall has deteriorated.
- Tough yellow/red nylon lugs have large bearing faces for superior strength and are specifically designed to ensure ease of clamping dry lining boxes with partitioning wall.

FEATURES

Compliant to BS 5733:2010 and CE

SPECIFICATIONS

VS-EVS-ACBBS VS-EVS-ACBBF Steel **Plastic** 1-Gang - for Single Gang ASSIST CALL devices 1-Gang Surface Box Gang **Earth Terminal** Fitted **ASSIST CALL devices ASSIST CALL devices** Use Knock-out cable entries to both sides, top and bottom -Knock-outs 5x 20 mm in addition to a 20 mm knock-out to the back of the box. Dimensions (W x H x D) 87 x 87 x 35 mm 87 x 87 x 35 mm Finish Steel White Plastic **Fixing Centre** 60.3 mm Flange Features a large flange to prevent slipping into cavity Tough Nylon Adjustable Lugs Lugs

73 x 73 mm

ORDERING INFORMATION

Product Code Product Description

VS-EVS-ACBBF Plastic Flush Mount Back-box for ASSIST CALL Stations (87 x 87 x 35 mm) VS-EVS-ACBBS Steel Surface Mount Back-box for ASSIST CALL Stations (87 x 87 x 35 mm)



Cut-out



STEEL SURFACE MOUNT BACK-BOX




The VS-EVS-OSBBS is a 2-Gang 41 mm deep metal back-box suitable for use with **Type B Outstations**, **Remote Alarm Panels and ASSIST CALL Controllers**.

It is ideal for surface fixing onto brick or block walling. The curvature of the corners is matched exactly to the product.

PLASTIC FLUSH MOUNT BACK-BOX

- The VS-EVS-OSBBF 2-Gang For Type B Outstations, Remote Alarm Panels and ASSIST CALL Controllers.
- The double 35 mm Dry lining Box is ideal for fast fixing into cavity wall structures, dry lining partitions and plaster board up to 15 mm thick. Manufactured from flame retardant



VS-EVS-OSBBS

 Tough yellow/red nylon lugs have large bearing faces for superior strength and are specifically designed to ensure ease of clamping dry lining boxes with partitioning wall.

FEATURES

Compliant to BS 5733:2010 and CE

SPECIFICATIONS

	Steel	Plastic
Gang	2-Gang surface box	2-Gang
Earth Terminal	Fitted	_
Use	ASSIST CALL Devices Type B Outstations	Type B Outstations Remote Alarm Panels ASSIST CALL Controller
Knock-outs	7x 20 mm	Knock-out cable entries to both sides, top and bottom – in addition to a 20 mm knock-out to the back of the box.
Dimensions (W x H x D)	147 x 87 x 35 mm	147 x 87 x 35 mm
Finish	Steel	White plastic
Fixing Centre	120.6 mm	_
Flange	_	Features a large flange to prevent slipping into cavity
Lugs	_	Tough Nylon Adjustable Lugs

VS-EVS-OSBBF

133 x 73 mm

ORDERING INFORMATION

Product Code Product Description

VS-EVS-OSBBF Plastic Flush Mount Back-box for Type B Refuge Stations (147 x 87 x 35 mm) Steel Surface Mount Back-box for Type B Refuge Stations (147 x 87 x 35 mm)

■ DISCLAIMER: Although the contents of our product literature have been prepared with the greatest care, Technoswitch can accept no liability whatsoever for any direct or indirect damages of any kind that may arise due to either errors or omissions in them, or amendments to products or other specifications following publication.

© Technoswitch (Pty) Ltd



Cut-out