



FLAME DETECTORS

FLAMESPEC IR3 FLAME DETECTOR



FLAMESPEC
IR3 FLAME DETECTOR

DESCRIPTION

FlameSpec IR3 flame detectors deliver ultra-fast response, high performance and reliable detection of all types of hydrocarbon fires (visible and non-visible).

The detector addresses slow-growing fires and the fast eruption of fire using improved triple IR technology. The detector operates in all weather and light conditions with the highest immunity to false alarms.

A non-EX version of the IR3 FlameSpec Detector is also available.

FEATURES

- Highest levels of false alarm immunity.
- Detects up to 80 metres for a 0.1 m² n-heptane pan fire.
- Hydrocarbon flame detection. Three wavelengths, in the infrared spectral range of 4.0 to 5.0 μm , with clear separation.
- Each sensor has the same field of view to improve false alarm immunity further.
- Ultra-fast detection mode – detection within 40 milliseconds for fireballs or explosions.
- Fast flame detection, <1.5s for standard fire up to 30 metres.
- Five selectable sensitivity levels.
- Universal outputs, 3- and 4-wire, 4-20 mA sink/source, Fire, Auxiliary and Fault Relays. RS485 port using Modbus RTU.
- Event logger – alarms and faults are logged to non-volatile memory.
- Built-in Test (BIT) – automatic and manual self-test of window cleanliness and overall detector operation.
- Dirty optics warning for preventive maintenance requirements.
- Window heater to prevent condensation and icing.
- Stainless steel tilt mount provides horizontal and vertical adjustment.
- SIL2 option available.
- Non-EX option available.
- HART® 7 for configuration and maintenance option available.
- 5-Year warranty.





FLAME DETECTORS

FLAMESPEC IR3 FLAME DETECTOR

SPECIFICATIONS

FIRE DETECTION	Detection Time & Distance	40 ms for fast fire burst or explosion 2.6 s for 0.1 m ² n-heptane pan fire at 0–30 m 7.1 s for 0.1 m ² n-heptane pan fire at 30–80 m
	Sensitivity Range	Five sensitivity ranges: Extreme, High, Medium, Low, Very Low
	Field of view (IR detection)	90° Horizontal, 75° Vertical
	Time Delay	Configurable 0-30 seconds
	Built-in Test	Automatic and Manual
ELECTRICAL	Operating Voltage	24 VDC nominal (18-32 VDC)
	Current Consumption	Standby: 120 mA 180 mA all systems in operation (including window heater)
	Electrical Entries	2x cable and conduit entries 3/4" NPT(F) or M25x1.5
	Wiring	12-20 AWG (2.5-0.35 mm ²)
OUTPUTS	Relays	SPST volt-free contacts rated 2A at 30 VDC 3 relays: Alarm & Auxiliary – normally open; Fault – normally closed
	0-20 mA (stepped) Current Output	3-wire and 4-wire (isolated) configurations (sink and source) HART® rev 7.0 (option available)
	Indication	Tri-colour LED (Green, Yellow, Red)
	Modbus	RTU compatible on RS485
MECHANICAL	Size	140 x 90 x 90 mm
	Weight	Detector (Stainless Steel 316): 3.0 kg Tilt mount (Stainless Steel 316): 1.5 kg
ENVIRONMENTAL	Temperature Range Humidity	Operating & Storage: –55°C to +85°C
	Humidity	Up to 99% (RH), non-condensing
	Ingress Protection	IP66 & 68 (2m, 24hr); NEMA 4X & 6P
APPROVALS	ATEX	ATEX: II 2 G D Ex db IIC T5 Gb or Ex db eb IIC T5 Gb and Ex tb IIIC T95°C Db –55°C < Ta < 75°C Ex db IIC T4 Gb or Ex db eb IIC T4 Gb and Ex tb IIIC T105°C Db –55°C < Ta < 85°C
	IECEX, INMETRO & PESO	Ex db IIC T5 Gb -50°C ≤ Ta ≤ 75°C Ex db IIC T4 Gb -50°C ≤ Ta ≤ 85°C
	FMus & FMc	Class I, Div. 1, Groups B, C & D; T4 Class I, Zone 1, AEx/Ex db IIC T4 Gb T4 -50°C ≤ Ta ≤ 85°C T5 -50°C ≤ Ta ≤ 75°C
	EAC CU TR	1Ex d IIC T5 Gb or 1Ex de IIC T5 Gb and Ex tb IIIC T95°C Db –55°C ≤ Ta ≤ 75°C 1Ex d IIC T4 Gb or 1Ex de IIC T4 Gb and Ex tb IIIC T105°C Db –55°C ≤ Ta ≤ 85°C
	Performance	ANSI FM 3260 EN 54-10
	Functional Safety	Complies to SIL2, per IEC 61508 (option available)
	MED	DNVGL Certificate Number MED-B-00006AM - units available upon request

ORDERING INFORMATION

Product Code	Product Description
FG-IR3-EXSS	IR3 Flame Detector: Hydrocarbon Fires, SS316
FG-IR3-SS	IR3 Flame Detector: Hydrocarbon Fires, <i>non-EX</i> , SS316
FG-WCSS-SD	Weather Cover: Standard Flame Detector, SS316
FG-AS-SD	Airshield: Standard Flame Detectors only
FG-FSIM-IR3-KIT	Flame Simulator Kit: IR3 Hydrocarbon Flame Detector

• **DISCLAIMER:** Although the contents of our product literature have been prepared with the greatest care, Technoswitch can accept no liability whatsoever for any direct or indirect damages of any kind that may arise due to either errors or omissions in them, or amendments to products or other specifications following publication. © Technoswitch (Pty) Ltd



HEAD OFFICE — JOHANNESBURG
Cussonia Park, 3 Ridge Road, Laser Park, Johannesburg T +27 (0)11 794 9144 E info@technoswitch.co.za
CAPE TOWN T +21 948 4575 DURBAN T +27 (0)31 266 8843

www.technoswitch.co.za

Document: DS-FG-IR3-EXSS-FG-IR3-SS-FlameSpec 20231005 E & OE